

Enclosures for multimedia and communication device DIDO ECG MEDIA

ENCLOSURE FOR MULTIMEDIA AND COMMUNICATION DEVICES

- Telephone connection
- Modems and routers (for wireless use plastic door!)
- Antenna, cable or satellite TV connection
- Included perforated mounting plate (zinc plated steel),
- Included installation accessories for concrete and hollow walls



Flush mounted multimedia distribution board - perforated metal door, white

Type	Code No.	Description	Weight [g]	Packaging [pcs]
ECG42COMB02/1-I	001100220	2 Media + 1 Modular row	3400	1
ECG56COMB03/1-I	001100221	3 Media + 1 Modular row	4100	1
ECG56COMB02/2-I	001100222	2 Media + 2 Modular rows	4100	1
ECG70COMB04/1-I	001100223	4 Media + 1 Modular row	4900	1
ECG70COMB03/2-I	001100224	3 Media + 2 Modular rows	4900	1
ECG70COMB02/3-I	001100225	2 Media + 3 Modular rows	5000	1

*Rear side plastics conforms 650°C glow wire test (not appropriate for wooden or hollow walls - IEC 60670-24)

Flush mounted multimedia distribution board - perforated metal door, white

Type	Code No.	Description	Weight [g]	Packaging [pcs]
ECG42HCOMB02/1-I	001100226	2 Media + 1 Modular row	3400	1
ECG56HCOMB03/1-I	001100227	3 Media + 1 Modular row	4100	1
ECG56HCOMB02/2-I	001100228	2 Media + 2 Modular rows	4100	1
ECG70HCOMB04/1-I	001100229	4 Media + 1 Modular row	4900	1
ECG70HCOMB03/2-I	001100230	3 Media + 2 Modular rows	4900	1
ECG70HCOMB02/3-I	001100231	2 Media + 3 Modular rows	5000	1

Conforms 850°C glow wire test according to IEC60670-24 for hollow wall installation

